

PRODUCT CODE

156217

LIFTEK®
SUPPLIED BY **SHS**

STACKER STRADDLE

1200KG
3.6M DUPLEX



- ✓ Modern, compact, robust, reliable, multipurpose stacker equipped with “plug and play” solutions
- ✓ H beam mast with two side cylinders for improved stability and visibility
- ✓ Faster lifting and lowering speeds delivering higher stacking performance and efficiency
- ✓ User-friendly cover with document, objects and cup pocket and optional USB port to charge any device
- ✓ Both AGM and lithium batteries available to suit different needs
- ✓ Integrated charger as standard offering charging convenience
- ✓ Market-proven drive unit for reliability assurance
- ✓ Mono mast and duplex mast in fork and straddle configurations to meet various needs

Manufacturer			LIFTEK	
Model designation			ESA121-M	ESA121-D
Drive			Electric	Electric
Load capacity	Q	kg	1200	1200
Load center distance	c	mm	600	600
Service weight		kg	490	826
Retracted mast height	h1	mm	1951	2425
Lift height	h3	mm	1530	3730
Length to face of forks	l2	mm	592	650
Overall width	b1/b2	mm	826	1156/1232/1308/1384
Fork dimensions	s/e/l	mm	60/170/1150	40/100/1070
Turning radius	Wa	mm	1452	1475
Max. gradeability, laden/unladen		%	3/10	3/10
Travel speed, laden/unladen		km/h	4.0/4.5	4.0/4.5
Lifting speed, laden/unladen		m/s	0.15/0.25	0.15/0.24
Lowering speed, laden/unladen		m/s	0.19/0.14	0.2/0.21
Battery voltage/nominal capacity		V/Ah	24/105	24/105

SHS
HANDLING SOLUTIONS

0800 619 0800
SALES@SHS-HANDLING.COM

SHSHANDLING
SOLUTIONS
.COM

SHS HANDLING SOLUTIONS LTD, ELEVATION HOUSE, UNIT C,
TINGEWICK ROAD INDUSTRIAL PARK, BUCKINGHAM, MK18 1SU