

PRODUCT CODE

22796

LIFTEK®
SUPPLIED BY **SHS**

JX0 | JX0-30

ELECTRIC ORDER
PICKER



- ✓ Intuitive driving system and controls
- ✓ Compact size and small turning radius for usage in tightest spaces
- ✓ High capacity electric powered load tray
- ✓ Great ergonomic design with spacious operator compartment and comfortable bucket gates
- ✓ Maximum safety with automatic gate locking, operator sensors and blue spot light
- ✓ 24V Li-Ion battery option: grant efficiency, long autonomy and opportunity charging

Manufacturer			Liftek®	Liftek®
Model designation			JX0/JX0-30(Lead acid)	JX0/JX0-30(Li-ion)
Drive			Electric	Electric
Load capacity	Q	kg	90/110/136	90/110/136
Wheelbase	y	mm	1095	1095
Service weight		kg	800	800
Height of overhead/ guard cabin	h6	mm	1425	1425
Lift height	h3	mm	3615	3615
Height, mast extended	h4	mm	4090	4090
Overall length	l2	mm	1440	1440
Overall width	b1/b2	mm	750	750
Stand height, elevated	h12	mm	3000	3000
Turning radius	Wa	mm	1260	1260
Travel speed, laden/unladen		km/h	6/6.5	6/6.5
Lifting speed, laden/unladen		m/s	0.22/0.27	0.22/0.27
Lowering speed, laden/unladen		m/s	0.31/0.25	0.31/0.25
Max. gradeability, laden/unladen		%	5/8	5/8
Drive motor rating S2 60 min		kW	0.65	0.65
Battery voltage/nominal capacity		V/Ah	24/120	24/135

SHS
HANDLING SOLUTIONS

0800 619 0800
SALES@SHS-HANDLING.COM

SHSHANDLING
SOLUTIONS
.COM

SHS HANDLING SOLUTIONS LTD, ELEVATION HOUSE, UNIT C,
TINGEWICK ROAD INDUSTRIAL PARK, BUCKINGHAM, MK18 1SU



FEATURES

SAFE AND EFFICIENT ASSISTANT FOR ORDER PICKING

The safe, practical and efficient alternative to ladder, traditional order pickers and working platform, XO/JXO-30 is the perfect truck for operations in busy and confined spaces which helps minimize travelling and picking time. XO/JXO-30 offers a working height of 5 meters and a picking height of 4,5 meters, suitable for high rack system in small to large warehouses.



INTUITIVE DRIVING SYSTEM AND CONTROLS

Effortless, intuitive and precise driving through mini steering (left side) and driving direction and speed control (right side). Platform and load tray controls buttons are located in comfortable position. The LCD display shows battery status, driving and turning direction, hourmeter. At every start JO/JXO-30 automatically regulate to straight driving direction.



COMPACT SIZE AND ERGONOMIC DESIGN

The compact size, the effortless driving and the 180° steering allow XO/JXO-30 to work in extremely narrow spaces in an easy and comfortable way. The spacious operator compartment and the fingertip controls make the XO/JXO-30 an ergonomic machine allowing long and fatigue-free operation.



SAFETY AND PERFORMANCE

Driving and lifting can be done simultaneously for the maximum efficiency and travelling speed is automatically regulated based on the operator lifting height. Several sensors allow for verifying the correct working position and the gate lock, and unlocking automatically based on the lifting position. XO/JXO-30 comes with the blue spot light and buzzer to comply with the highest safety standard.



LITHIUM BATTERY OPTION AVAILABLE

XO delivers 24V/135Ah maintenance-free lithium battery option which is the suggested choice for the XO order picker: in combination with single-phase 24V-30A integrated charger, JXO/JXO-30 allows long operating time with fast opportunity charging.





JX0/JX0-30


If there are improvements of technical parameters or configurations, no further notice will be given.
The diagram shown may contain non-standard configurations.

The diagram shown may contain non-standard configurations.



ELECTRIC ORDER PICKER

JX0/JX0-30





OPTION:

No.	Optional items	JX0/JX0-30
2.1	Load wheel type	●Single
2.2	Load wheel material	●Rubber
2.3	Drive wheel material	●PU
2.7	Battery capacity	●120Ah Gel battery ○135Ah Li-ion battery
2.8	Charger	●24V-15A integrated charger for Gel battery ○24V-30A integrated charger for Li-ion battery
2.9	Battery indicator	●With time
2.14	Electrostatic chain	●No
3.3	Castor wheels	●Yes and not customized
3.9	Blue lamp	●Front blue lamp
3.12	Buzzer	●Drop buzzer ○Running buzzer ○Reversing buzzer
3.18	Guide wheel	●No ○Yes and not customized
3.20	Step on the safety switch with both feet	●No ○Yes and not customized
4.7	Overhead guard	●No
Note : ●Standard ○ Optional - Inconformity		

AT SHS, WE HELP COMPANIES MOVE GOODS SAFELY AND EFFICIENTLY BY DESIGNING, SUPPLYING, AND MAINTAINING MATERIALS HANDLING EQUIPMENT.