

- Suitable for EURO, CHEP and UK sizes pallets
- <u>Channel-reinforced frame for optimal fork alignment reducing the risk of accidents and damage.</u>
- Tandem Load Rollers distribute weight evenly, making it easier to manoeuvre heavy loads, helping reduced operator effort and increase productivity.
- High-quality German hydraulic pump with slow lowering hand contol and 3-position lever.
- Mylon entry and exit rollers minimise physical strain, for operator comfort and reduced injury risk.
- Full 12-month parts and labour warranty, proving peace of mind and ongoing support.

MANUFACTURER'S DATA AND DESIGN CHARACTERISTICS

Characteristics	2407
Manufacturer	LIFTEK
Model	Manual Pallet Truck
Type of Operation	Pedestrian
Load Capacity	3000kg
Minimum Fork Lift Height	85mm
Maximum Fork Lift Height	190mm
Size of Fork	60mm
Overall Fork Width	550mm
Fork Length	1150mm

AT SHS, WE HELP COMPANIES MOVE GOODS **SAFELY** AND **EFFICIENTLY** BY **DESIGNING**, **SUPPLYING**, AND **MAINTAINING** MATERIALS HANDLING EQUIPMENT.



© 0800 619 0800

☑ SALES@SHS-HANDLING.COM

